



 **E-BERK**

**E-BERK**



**E-MSV**



**MULTI - PURPOSE  
TUNNEL SERVICE  
VEHICLE**

# MULTI - PURPOSE TUNNEL SERVICE VEHICLE



## Technical Specifications

Our MSV machines can be customized within the scope of your projects.

### E-TSV40

#### Dimensions

● Width	1700 mm
● Height (Loaded)	2560 mm
● Length	22185 mm

### E-TSV40

#### Weight

● Unloaded Weight	19000 kg
● Standard Carrying Capacity	40000 kg
● Maximum Carrying Capacity	50000 kg
● Maximum Total Load Capacity to be transported	69000 kg

#### Performance for 40 Tons of Load

● Maximum Slope With Loaded Moveable	12% Movement
● Unloaded Weight Speed at 5% Positive Slope	20 km/h
● Unloaded Weight Speed on Flat Terrain	24 km/h
● Loaded Weight Speed at 5% Positive Slope	10 km/h
● Loaded Weight Speed on Flat Terrain	15 km/h
● Maximum Climbing Gradient in Motion	16 %

The standard of diesel engines is stage 5 tier 4.

The machine has been manufactured in accordance with safety regulations.



### E-TSV20

#### Dimensions

● Width	1700 mm
● Height (Loaded)	2560 mm
● Length	17850 mm

### E-TSV20

#### Weight

● Unloaded Weight	8000 kg
● Standard Carrying Capacity	20000 kg
● Maximum Carrying Capacity	22000 kg
● Maximum Total Load Capacity to be transported	30000 kg

#### Performance for 20 Tons of Load

● Maximum Slope With Loaded Moveable	12% Movement
● Unloaded Weight Speed at 5% Positive Slope	16 km/h
● Unloaded Weight Speed on Flat Terrain	20 km/h
● Loaded Weight Speed at 5% Positive Slope	7 km/h
● Loaded Weight Speed on Flat Terrain	9 km/h
● Maximum Climbing Gradient in Motion	16 %



[www.e-berk.com](http://www.e-berk.com)
[e-berk@e-berk.com](mailto:e-berk@e-berk.com)
[+90 312 267 48 48](tel:+903122674848)  
[Maliköy Anadolu Osb Mah. 12. Cad. No:24 Sincan / ANKARA / TÜRKİYE](#)



Cert:21IQJ14  
ISO 9001:2015

Cert:21IEJB24  
ISO 14001:2015

Cert:21IOJF22  
ISO 45001:2018

